

vario 1"

The vario switching unit for pressurised water units up to 200 °C.

- Water connections G 1"
- Eliminate tie lines
- High gloss surfaces
- Filling / spraying of complex cavities
- Shortening the cycle times



Technical specifications

Outlet temperature	Heat transfer medium	Connection compressed air	Connections
200 °C	Water	G 1/4" (IG)	G 1" / BSP 60°

Technical data

Outlet temperature		
max.	°C	200
Heat transfer medium		Water
Operating voltage	V/Hz	110-240 V, 50/60 Hz, 1PE
Ext. control voltage	V	24 VDC
Connection compressed air		G 1/4" (IG)
Range compressed air	bar	4 - 10
Connections		G 1" / BSP 60°
Inlet TCU COLD		G 1" / BSP 60°
Inlet TCU HOT		G 1" / BSP 60°
Outlet TCU COLD		G 1" / BSP 60°
Outlet TCU HOT		G 1" / BSP 60°
Inlet consumer COLD		G 1" / BSP 60°
Inlet consumer HOT		G 1" / BSP 60°
Outlet consumer COLD		G 1" / BSP 60°
Outlet consumer HOT		G 1" / BSP 60°
Pressure controlled valves		2/2 Ways, 1", 200 °C
Degree of protection		IP40
Dimensions W/H/D	mm	266/705/822
Weight	kg	48
Color	RAL	9006/7016
Ambient temperature		
max.	°C	40

Standard equipment

- Water circuit of non-rusting materials
- Unit in IP40 protection degree

Options

Principle Scheme*

Representation Switzerland

Injection Molding, Die Casting, other Applications

Regloplas AG
Spühlstrasse 6
9016 St. Gallen
Switzerland

Tel +41 71 282 58 00
Email info@regloplas.com