

# coldWater 160

The temperature control solution for variothermal temperature control with water up to 160 °C

- Rapid cooling of the mould
- Cooling temperatures below 40 °C
- Operating temperature up to 160 °C of the heat transfer medium
- Shortening of cycle times
- The use of the coldWater unit reduces the cost of ownership of the machine
- Ideally, the coldWater can be combined with the energyBattery in the variothermal process



## Technical specifications

System water temperature	Heat transfer medium	Pump capacity/Type			Connections	
160 °C	Water	CRI 3H	50 l/min	0.75 kW	G3/4"	G3/4"

## Technical data

<b>Outlet temperature</b>		
max.	°C	160
<b>Heat transfer medium</b>		Water
<b>Pump capacity/Type</b>		CRI 3H
Flow rate max.	l/min	50
Power consumption	kW	0.75
Pressure max.	bar	4.6
<b>Operating voltage</b>	V/Hz	380-415 V, 50 Hz   440-480 V, 60 Hz
<b>Connections</b>		
Outlet/Inlet		G3/4"
Cooling water mains		G3/4"
<b>Dimensions W/H/D</b>	mm	317/820/748
<b>Degree of protection</b>		IP40
<b>Weight</b>	kg	48
<b>Ambient temperature</b>		
max.	°C	40
<b>Noise level</b>	db (A)	< 70

## Standard equipment

## Options

## Representation Switzerland

### Injection Molding, Die Casting, other Applications

Regloplas AG  
Spühlstrasse 6  
9016 St. Gallen  
Switzerland

Tel +41 71 282 58 00  
Email [info@regloplas.com](mailto:info@regloplas.com)