

multiFlow modular Die-casting 120

The multi distributor system from REGLOPLAS is fully integrated into the control system of temperature control units with sensors, monitoring, displays and controllers. Each circuit is set and monitored individually.

- Control system RT100 and RT200
- Water distribution system up to 120 °C
- 4 to 16 cooling channels per temperature control unit
- Flow per channel 1 l/min - 40 l/min
- Integrated volume flow and temperature measurement per channel



Technical specifications

Outlet temperature	Heat transfer medium	Number of channels	Flow measurements per channel (Typ)	Connections
120 °C	Water	4 - 16	1 - 18 (VFS) l/min 2 - 40 (VFS) l/min	G1 1/2" 60° Cone G1/2" 60° Cone

Technical data

Outlet temperature		
max.	°C	120
Heat transfer medium		
Water		
Number of channels		
4 - 16		
Sensors		
Flow measurement per channel (Typ)	l/min	1 - 18 (VFS) 2 - 40 (VFS)
Temperature measurement per channel		
PT100		
Models		
Cooling channels		
4 / 6 / 8 / 10 / 12 / 14 / 16		
Direction of outgoing channels		
to the right or the left		
Control system		
RT100 / RT200		
Operating voltage	V/Hz	24V DC
Connections		
Main connection temperature control unit		
G1 1/2" 60° Cone		
Outlets to consumer		
G1/2" 60° Cone		
Degree of protection		
IP45		
Dimensions W/H/D		
4-fold	mm	425/236/348
16-fold	mm	425/236/948
Color	RAL	7016
Ambient temperature		
max.	°C	40
Noise level	db (A)	--

Standard equipment

- Profinet interface connection to temperature control unit

Options

- Blow out
- Siemens Touch Display 9" "multiControl"
- Main connection temperature control unit: G1" 60° Cone, G3/4" 60° Cone, G11/4" IG
- Outlets (right or left): G1/2" IG, M22x1.5 (15l)
- Stand-alone with control system RT200

Representation Switzerland

Injection Molding, Die Casting, other Applications

Regloplas AG
Spühlstrasse 6
9016 St. Gallen
Switzerland

Tel +41 71 282 58 00
Email info@regloplas.com