

P141XL

Pressurised-water temperature control unit up to 140 °C

- Control system RT200
- Pump with high flow rate: 200 l/min
- Low-scaling cooling system "SK"
- Pressure control
- Solid-state relay instead of heating contactor



Technical specifications

Heat transfer medium	Outlet temperature	Heating capacity at 400V	Cooling capacity		Pump capacity/Type		
Water	140 °C	20 / 40 / 60 kW	130 °C	115 kW	SG85	200 l/min	3.5 kW

Technical data

Outlet temperature		
max.	°C	140
Heat transfer medium		Water
Filling quantity	l	10
Expansion volume	l	5.0
Heating capacity at 400V	kW	20 / 40 / 60
Cooling capacity	kW	115
Cooler		SK
at outlet temperature	°C	130
at cooling water temperature	°C	20
Pump capacity/Type		SG85
Flow rate max.	l/min	200
Power consumption	kW	3.5
Pressure max.	bar	5.3
Control system		RT100 / RT200
Measuring mode (standard)		Pt100
Operating voltage	V/Hz	200-600 V, 50/60 Hz
Connections		
Outlet/Inlet		G1 1/2"IG
Cooling water mains		G3/4"
Degree of protection		IP54
Dimensions W/H/D	mm	432/1350/1554
Weight	kg	265
Color	RAL	9006/7016
Ambient temperature		
max.	°C	40
Noise level	db (A)	< 70


Standard equipment

- Solid-state relay (SSR) instead of heating contactor
- Hand valve in inlet and outlet
- Water circuit of non-rusting materials
- Automatic water refill
- Filter in the main circuit
- Filter in cooling water circuit
- Patented low-scale cooling system (SK)
- Pressure gauge outlet
- Pressure gauge for system pressure
- Unit in IP54 protection degree
- RT200 control system


Options

- Electronic flow measurement
- RT100 control system

Pump curve



Cooling curve



Representation Switzerland

Injection Molding, Die Casting, other Applications

Regloplas AG
 Spühlstrasse 6
 9016 St. Gallen
 Switzerland

Tel +41 71 282 58 00
 Email info@regloplas.com