

P180LD

Dual zone pressurised-water temperature control unit up to 180 °C

- Control system RT200 with 2 seperate displays
- Robust pump with flow rate of 80 l/min
- Low-scaling cooling system "SK"
- Pressure control
- Leak-free pump with magnetic coupling
- Solid-state relay instead of heating contactor



Technical specifications

Heat transfer medium	Outlet temperature	Heating capacity at 400V	Cooling capacity		Pump capacity/Type		
Water	180 °C	17 kW	170 °C	76 kW	SM82H	80 l/min	2.8 kW
			170 °C	90 kW			

Technical data

Outlet temperature			
max.	°C	180	
Heat transfer medium		Water	
Filling quantity	l	3.0	
Expansion volume	l	2.0	
Heating capacity at 400V	kW	17	
Cooling capacity	kW	76	90
Cooler		SK	2SK
at outlet temperature	°C	170	170
at cooling water temperature	°C	20	20
Pump capacity/Type		SM82H	
Flow rate max.	l/min	80	
Power consumption	kW	2.8	
Pressure max.	bar	9.0	
Control system		RT100 / RT200	
Measuring mode (standard)		Pt100	
Operating voltage	V/Hz	400 V, 50 Hz, 3 PE	
Connections			
Outlet/Inlet		G3/4"	
Cooling water mains		G1/2"	
Degree of protection		IP54	
Dimensions W/H/D	mm	507/1167/1492	
Weight	kg	280	
Color	RAL	9006/7016	
Ambient temperature			
max.	°C	40	
Noise level	db (A)	< 70	


Standard equipment

- Solid-state relay (SSR) instead of heating contactor
- Filter in the main circuit
- Pressure gauge for system pressure
- Draining the consumer by suction
- Leak-free pump
- Patented low-scale cooling system (SK)
- Unit in IP54 protection degree
- RT200 control system


Options

- Electronic flow measurement
- Hand valve in inlet and outlet
- Pump control
- RT100 control system

Pump curve



Cooling curve



Representation Switzerland

Injection Molding, Die Casting, other Applications

Regloplas AG
Spühlstrasse 6
9016 St. Gallen
Switzerland

Tel +41 71 282 58 00
Email info@regloplas.com