

P160LD

Dual zone pressurised-water temperature control unit up to 160 °C

- Control system RT200 or RT100 with 2 separate displays
- Robust pump with flow rate of 80 l/min
- Low-scaling cooling system "SK"
- Pressure control
- Solid-state relay instead of heating contactor
- Heavy particle separator in the inlet



Heat transfer medium	Outlet temperature	Heating capacity at 400V	Cooling capacity		Pump capacity/Type		
			150 °C	66 kW	SM82	80 l/min	2.8 kW
Water	160 °C	17 kW	150 °C	78 kW			

Technical data			
Outlet temperature			
max.	°C	160	
Heat transfer medium		Water	
Filling quantity	l	3.0	
Expansion volume	l	2.0	
Heating capacity at 400V	kW	17	
Cooling capacity	kW	66	78
Cooler		SK	2SK
at outlet temperature	°C	150	150
at cooling water temperature	°C	20	20
Pump capacity/Type		SM82	
Flow rate max.	l/min	80	
Power consumption	kW	2.8	
Pressure max.	bar	9.0	
Control system		RT100 / RT200	
Measuring mode (Standard)		Pt100	
Operating voltage	V/Hz	400 V, 50 Hz, 3 PE	
Connections			
Outlet/Inlet		G3/4"	
Cooling water mains		G1/2"	
Degree of protection		IP54	
Dimensions W/H/D	mm	507/1167/1492	
Weight	kg	280	
Color	RAL	9006/7016	
Ambient temperature			
max.	°C	40	
Noise level	db (A)	< 70	

Standard equipment

- Solid-state relay (SSR) instead of heating contactor
- Filter in the main circuit
- Pressure gauge for system pressure
- Drainage of the fluid from the consumer by suction
- Leak-free pump
- Patented low-scale cooling system "SK"
- Unit in IP54 protection degree

Options

- Electronic flow measurement
- Manual shut-off valve in the inlet and outlet
- Pump control