

vario SPS 3/4"

The vario switching unit for pressurised water units up to 200 °C.

- Water connections G 3/4 "
- Eliminate tie lines
- High gloss surfaces
- Filling / spraying of complex cavities
- Shortening the cycle times
- Siemens PLC controlled control system with touch screen



Outlet temperature
200 °C

Heat transfer medium
Water

Connection compressed air
G 1/4"

Connections
G 3/4" / BSP 60°

Technical data		
Outlet temperature		
max.	°C	200
Heat transfer medium		Water
Control system		Siemens S7-1200
Operating voltage	V/Hz	110-240 V, 50/60 Hz, 1PE
Ext. control voltage	V	24 VDC
Connection compressed air		G 1/4"
Range compressed air	bar	4 - 10
Connections		G 3/4" / BSP 60°
Inlet TCU COLD		G 3/4" / BSP 60°
Inlet TCU HOT		G 3/4" / BSP 60°
Outlet TCU COLD		G 3/4" / BSP 60°
Outlet TCU HOT		G 3/4" / BSP 60°
Inlet consumer COLD		G 3/4" / BSP 60°
Inlet consumer HOT		G 3/4" / BSP 60°
Outlet consumer COLD		G 3/4" / BSP 60°
Outlet consumer HOT		G 3/4" / BSP 60°
Pressure controlled valves		2/2-Weg, 3/4", 200 °C
Degree of protection		IP40
Dimensions W/H/D	mm	203/563/742
Weight	kg	34
Color	RAL	9006/7016
Ambient temperature		
max.	°C	40

Standard equipment

Water circuit of non-rusting materials
Unit in IP40 protection degree

Options

Regloplas energyBattery unit
Regloplas coldWater unit